

RIEGL LD90-3100HS general purpose distance meter

LD90-3100HS

High-Speed distance meter for robotics applications, automatic anti-collision systems, etc.

Measuring range depending on the reflection coefficient ρ of the target	
good, diffusely reflecting targets, $\rho \geq 80\%$	up to 150 m ¹⁾
bad, diffusely reflecting targets, $\rho \geq 10\%$	up to 50 m ¹⁾
Reflecting foil ²⁾ or plastic cat's-eye reflectors	> 1000 m
Minimum distance, typically	1 m

Accuracy ³⁾ typically ± 15 mm, in the worst case ± 50 mm

Measuring time (ms or s) ⁴⁾ 5ms 10ms 20ms 50ms 0.1 0.2 0.5 1

Statistical deviation (mm) ⁵⁾ ± 30 ± 20 ± 15 ± 10 ± 7 ± 5 ± 3 ± 2

Resolution (mm) ^{5) 6)} 20 20 10 10 5 5 2 2

Divergence of the infrared measuring beam ⁷⁾ 1.8 mrad

Laser product classification according to IEC60825-1:2007

The following clause applies for instruments delivered into the United States:
Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007.

CLASS 1
LASER PRODUCT

- 1) typical values for average conditions. In bright sunlight, the operational range is considerably shorter than under an overcast sky. At dawn or at night the range is even higher.
- 2) reflecting foil 3M 3000X or equivalent, minimum dimensions 0.45 x 0.45 m²
- 3) standard deviation, plus distance depending error ≤ 20 ppm
- 4) selectable via RS232/RS422
- 5) depending on measuring time
- 6) chosen automatically by the internal microprocessor
- 7) 1 mrad corresponds to 10 cm beamwidth per 100 m of distance

Selectable data processing modes

The characteristics of the instrument can be adapted to the actual measurement situation by choosing between four different data processing programs:

The program FAST enables the quickest possible measurement at undisturbed conditions simply by averaging the single-pulse distance values which are acquired within the selected measuring time.

The program STANDARD provides a very useful clutter suppression: occasional echo signals caused not by the target itself but by

backscattering of particles between target and instrument (e.g. clouds of material in a dusty silo, or raindrops and snowflakes in free air) are eliminated and not taken into account.

The program MAXIMUM DISTANCE is optimized for undisturbed level measurements in a silo at the cost of a slightly higher acquisition time.

The program MINIMUM DISTANCE is ideal for measurements to small targets which are not easy to aim at, as it eliminates background echoes.

General technical data and dimensions as given in our general data sheet LD90-3 series.

Information contained herein is believed to be accurate and reliable. However, no responsibility is assumed by RIEGL for its use. Technical data are subject to change without notice. Data sheet RIEGL LD90-3100HS, 25/03/2010



RIEGL
LASER MEASUREMENT SYSTEMS
www.riegl.com

RIEGL Laser Measurement Systems GmbH, A-3580 Horn, Austria
Tel.: +43-2982-4211, Fax: +43-2982-4210, E-mail: office@riegl.co.at
RIEGL USA Inc., Orlando, Florida 32819, USA
Tel.: +1-407-248-9927, Fax: +1-407-248-2636, E-mail: info@rieglusa.com
RIEGL Japan Ltd., Tokyo 1640013, Japan
Tel.: +81-3-3382-7340, Fax: +81-3-3382-5843, E-mail: info@riegl-japan.co.jp