


RIEGL LD90-3200HiP-GF "High Penetration" level meter

LD90-3200HiP-GF <i>equipped with optical head MK42:</i> Laser Distance Meter for use with or without reflectors which, because of its "High Penetration" facility under conditions of bad visibility, is especially well suited for level measurements in large silos, distance measurement on cranes, etc. ¹⁾	Measuring range depending on the reflection coefficient ρ of the target ²⁾³⁾	good, diffusely reflecting targets, $\rho \geq 80\%$	up to 600 m
		bad, diffusely reflecting targets, $\rho \geq 10\%$	up to 200 m
		Reflecting foil ⁴⁾ or plastic cat's-eye reflectors	2000 m
	Minimum distance ⁵⁾		1 m
	Accuracy ^{6) 7)}	typically ± 25 mm, in the worst case ± 75 mm	
	Resolution		2 mm
	Measuring time (s) ⁸⁾	0.3 0.5 1 2	
	Statistical deviation (mm) ⁹⁾	± 20 ± 15 ± 10 ± 7	
	Divergence of the infrared measuring beam ¹⁰⁾		approx. 4.7 mrad
	Laser product classification according to IEC60825-1:2007		
The following clause applies for instruments delivered into the United States: Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007.			
Data interface	RS232 & RS422 (selectable), baud rate between 300 Bd and 38.4 kBd		

- 1) last, first, or strongest target return selectable
- 2) Typical values for average conditions. In bright sunlight, the operational range is considerably shorter than under an overcast sky. At dawn or at night the range is even higher.
- 3) target size \geq beam diameter
- 4) reflecting foil 3M680 or equivalent, dimensions 0.45 x 0.45 m²
- 5) minimum distance 5 m for full accuracy with retroreflecting targets
- 6) standard deviation, plus distance depending error 20 ppm
- 7) ≥ 5 min after power up
- 8) adjustable via RS232/RS422 or self-adapting
- 9) depending on measuring time
- 10) 1 mrad corresponds to 10 cm increase of beamwidth per 100 m of distance

General technical data and dimensions as given in our general data sheet LD90-3-GF series.

Information contained herein is believed to be accurate and reliable. However, no responsibility is assumed by RIEGL for its use. Technical data are subject to change without notice. Data sheet RIEGL LD90-3200HiP-GF, 25/03/2010



RIEGL
 LASER MEASUREMENT SYSTEMS
www.riegl.com

RIEGL Laser Measurement Systems GmbH, A-3580 Horn, Austria
 Tel.: +43-2982-4211, Fax: +43-2982-4210, E-mail: office@riegl.co.at
 RIEGL USA Inc., Orlando, Florida 32819, USA
 Tel.: +1-407-248-9927, Fax: +1-407-248-2636, E-mail: info@rieglusa.com
 RIEGL Japan Ltd., Tokyo 1640013, Japan
 Tel.: +81-3-3382-7340, Fax: +81-3-3382-5843, E-mail: info@riegl-japan.co.jp