

RiHYDRO

for commercial hydrographic and bathymetric surveying


- Automatic classification of water surface points
- Generation of a water surface model (WSM) based on classified water surface points
- Refraction correction of points below the water surface model (WSM)
- Support of different import and export formats for classification purposes
- Use point clouds from different scanners to identify water surface points
- Import externally generated WSM
- Processes a large number of files for unattended operation in batch mode
- Smoothly integrated into RiPROCESS

For smooth processing of scan data acquired with **RIEGL** Hydrography Laser Scanners the Airborne Data Processing Software AddOn **RiHYDRO** is offered as supplement to **RiPROCESS**.


When processing bathymetric laser data, additional processing steps have to be applied since both, the laser beam's refraction at the air-water interface and the lower propagation speed within the water column must be taken into account in order to obtain a geometrically correct point cloud. Those specific processing steps – usually called "refraction correction" – have to be carried out for each flight strip right after the standard ALS processing workflow.

Refraction correction of the points below the air-water interface (i.e. both points on the water bed and within the water column) requires a geometric **Water Surface Model (WSM)**. WSMs can be generated from the laser data by one of the tools offered with **RiHYDRO**. An alternative option is to import already existing water surface models. In the first case, the water surface points must be classified before. For this task, a specific point classification tool in **RiHYDRO** is provided, which allows classifying the points on horizontal water surfaces automatically.


The user can specify the index of refraction of the water and also a depth bias value to be taken into account during refraction correction.




visit our website www.riegl.com




Refraction Correction - Typical Workflow using RiHYDRO Tools




Profile view of classified water surface points



Maritime WSM visualized as normal vector field



Riverine WSM visualized as normal vector field



Refraction correction of targets below water surface

Classification of Water Surface Points

A tool for the automatic classification of water surface points is provided. Classification is based on identification of areas with layers of water surface points and subaqueous points. From such areas the classification of water surface points is extended to the entire water body.

Classification can be checked and modified manually in critical areas prior to the generation of a water surface model. Classification by third-party software is supported.

Generation of Water Surface Model (WSM)

Based on the classified water surface points, a geometric water surface model (WSM) is generated for each flight strip. For this task, a tool is available that allows the generation of a grid-based WSM containing height (and – optionally – normal vector) for each cell. This tool may be run in different modes, depending on whether standing water (sea, lakes) or riverine surfaces have to be handled.

Alternatively, already existing WSMs (i.e. generated by third-party software and given in a well-defined exchange format) may be imported by another tool.


Shift of Targets Below Water Surface to Correct Positions

Finally, the underwater targets have to be shifted to their correct positions according to refraction (beam bending and waveform compression). Therefore, a tool is available that is applied to each flight strip. Based on the underlying WSM, for each relevant ray, a representative plane is estimated and used to calculate the correction vector.

Optionally, all points, whose coordinates have been changed during this step, may be classified by this tool.

NEW TPU Estimator

In order to assess data quality, RiHYDRO now offers a tool for estimating the **Total Propagated Uncertainty (TPU)** for each measurement point. No additional environmental factors have to be entered for carrying out TPU estimation. This means, that TPU estimation provides a data quality check independently from the availability of reference data, access to the measurement area, or knowledge of local water condition. The tool TPU estimation is seamlessly integrated into the current workflow for both underwater and above-water data. The read-out of TPU is available as additional attribute data for each single point and a fully automated TPU report can be generated for the project.



RIEGL Laser Measurement Systems GmbH, Headquarters
RIEGL USA Inc., Headquarters North America

RIEGL Japan Ltd.
RIEGL China Ltd.
RIEGL Australia Pty Ltd.
RIEGL Canada Inc.

RIEGL UK Ltd.
RIEGL South America Spa
RIEGL Deutschland Vertriebsgesellschaft mbH

Contact us

