

Terrestrial Laser Scanning

NEW



RIEGL VZ-1200i


Fast Scans. Long Range. Maximum Efficiency.



RIEGL VZ-1200i

RIEGL's latest addition to the new generation of professional Terrestrial Laser Scanners stands for extreme versatility, high productivity, ultimate performance, and additional mobility.

High-Speed Meets Long-Range: The Next Level of RIEGL Laser Scanning.




High Productivity

- 60 scan positions per hour (with image acquisition)
- One-Touch button operation
- RIEGL VZ-i Project Map App for scan project monitoring
- simultaneous scan and image data acquisition
- Real-Time on-board automatic registration
- One-Touch Processing Wizard in RiSCAN PRO for automatic production of detailed PDF-report




Ultimate Performance

- achieve even longer measurement ranges at high scanning speed
- broad range capability (0.5 m up to 1800 m)
- **less than 30 seconds for a "Panorama_6mm"-scan with more than 30 mio 3D-measurements and up to 450 m measuring range**
- pulse repetition rate up to 2.2 MHz
- 3D position accuracy up to 3 mm @ 50 m
- scan speed up to 420 lines/sec
- high speed data download of up to 500 MB/sec



Extreme Versatility

- ideal for fast measurements combined with long measurement range
- low power 2200 kHz program for short range applications
- internal cameras and GNSS receiver
- lightweight (approx. 6 kg / 13 lbs)
- prepared for user-specific Python apps



Additional Mobility


- ideal for (optional) kinematic operation
- prepared for robotic operation (ROS driver available)
- flexible mounting platforms

Extreme Versatility – Key Applications

The RIEGL VZ-1200i is a very powerful eye-safe laser class 1 laser scanner. It combines a very long measuring distance with a very high scanning speed.

This makes it the perfect tool for all applications that require fast acquisition of high-resolution measurement data over long distances of up to 450 m (for "Panorama_6mm"-scans) and up to 700 m (for "detail scans"). Its suitability for kinematic data acquisitions further expands its range of applications.

You can use your RIEGL VZ-1200i in static mode to move the tripod every minute (Panorama 6 mm scan pattern: 6 mm resolution at a distance of 10 m, with simultaneous panorama photo acquisition) or in kinematic mode on mobile platforms with RTK-GNSS accuracy. **That is what we call versatility.**




Examples – using the scanner in static as well as in kinematic mode – include:


- mapping of topography and infrastructure (bridges, roads, railway lines, large construction sites, etc.)
- recording topography and infrastructure of coastlines and in ports (kinematic surveying from a boat)
- kinematic mapping of corridors
- data collection in alpine regions (low weight enables convenient transport; high measuring speed and long measuring ranges for fast data acquisition)
- data collection at landfills and storage sites for bulk materials (static and kinematic data acquisition)

High Productivity – Rapid Data Acquisition

up to 60 scan positions per hour



VZ-i Project Map App




VZ-i Project Map App

Key Features of rapid data acquisition with the RIEGL VZ-1200i:

- up to 60 scan positions per hour in combination with a maximum measuring range of 450 meters
- standard scan pattern: 6 mm resolution @ 10 m distance
- simultaneous image acquisition for high resolution panorama images
- real-time on-board automatic registration, no tablet required
- no tie points necessary for robust registration
- remote control by the use of the RIEGL VZ-i Series App (for iOS and Android)
- monitor registration with the VZ-i Project Map App (direct from the scanner)

High Productivity – Swift Data Processing


Produce end deliverables with the Data Processing Software RiSCAN PRO and its One-Touch Processing Wizard.




RiSCAN PRO – One-Touch Processing Wizard

Key Features of the Data Processing Software RiSCAN PRO:

- One-Touch Processing Wizard
- fast download from the CF-Express Card (up to 500 MB/sec)
- automatic filtering (e.g. dynamic objects, deviation, reflectance, multiple targets, etc.)
- optimization of the camera mounting calibration
- automatic colorization of the point cloud
- generation of ortho plots (e.g. GeoTIFF)
- export as RiPANO project, e57 project, LAS, etc.
- automatic generation of PDF report



colored point cloud



top view, x-ray visualization

Key Components

Front View



beam exit window

3 internal cameras

Rear View



7 inch touch screen (1280 x 800 pixel)

single button for convenient handling

1 rechargeable battery at each side

quick mounting adapter

Optional Equipment



GNSS RTK antenna

With an attached GNSS RTK antenna, the absolute positioning accuracy can be improved to 1-2 cm. The correction data is then received via WLAN. The GNSS RTK antenna is available in versions with and without an external camera.



Charger for 2 or 6 batteries

The chargers are designed for 2 or 6 batteries. They can be supplied from the 12 V DC voltage of a vehicle (additional cable necessary) as well as from a corresponding 110/230 V AC power supply module. The advantage of the 2-fold charger lies in the size and weight, that of the 6-fold charger in the possibility of continuous scanning over 24 hours (with simultaneous charging of the empty batteries).

Optional Equipment



Ultimate Performance – Technical Data

Laser Product Classification

Class 1 Laser Product according to IEC 60825-1:2014	The following clause applies for instruments delivered into the United States: Complies with 21 CFR 1040.10 and 1040.11 except for conformance with IEC 60825-1 Ed.3., as described in Laser Notice No. 56, dated May 8, 2019.	
--	--	---

Range Measurement Performance

Measuring Principle / Mode of Operation	time of flight measurement, echo signal digitization, online waveform processing		
Laser Pulse Repetition Rate (PRR) – (peak) ¹⁾	2200 kHz (Standard)	1200 kHz	300 kHz
Max. Measuring Range ^{2) 3)} natural targets $p \geq 90\%$ natural targets $p \geq 20\%$	740 m 360 m	970 m 480 m	1800 m 920 m
Minimum Range ⁴⁾	1.5 m / 0.5 m ⁵⁾	2 m	2.5 m
Max. Number of Targets per Pulse ⁶⁾	5	10	15
Precision ^{7) 8)}	3 mm	3 mm	3 mm
Ranging Accuracy ^{8) 9)}	5 mm		
3D Position Accuracy ¹⁰⁾	3 mm @ 50 m, 5 mm @ 100 m		
Laser Wavelength	near infrared, invisible		
Laser Beam Divergence	0.35 mrad ¹¹⁾ / 0.25 mrad ¹²⁾		

- 1) Rounded values.
- 2) Typical values for average conditions. Maximum range is specified for flat targets with size in excess of the laser beam diameter, perpendicular angle of incidence, and for atmospheric visibility of 23 km.
- 3) Due to the rotation of the scanning mirror and the time-of-flight of the laser pulses, there is an additional restriction on the maximum achievable measuring range.
max. meas. range [m] $\leq \frac{185000}{\text{scan speed line/sec}}$
- 4) Minimum range specified for vertical zenith angles from 25 deg to 130 deg, resp. 105° vertical field of view.

- 5) 2200 kHz measurement program with reduced laser power
- 6) If more than one target is hit, the total laser transmitter power is split and, accordingly, the achievable range is reduced.
- 7) Precision, also called reproducibility or repeatability, is the degree to which repeated measurements show the same result.
- 8) 1-sigma value under RIEGL test conditions.
- 9) Accuracy is the degree of conformity of a measured quantity to its actual (true) value.
- 10) 1-sigma value, based on target modelling, under RIEGL test conditions.

- 11) Measured at the 1/e2 points. 0.35 mrad corresponds to an increase of 35 mm of beam diameter per 100 m distance.
- 12) Measured at the 1/e points. 0.25 mrad corresponds to an increase of 25 mm of beam diameter per 100 m distance.

Scanner Performance

	Vertical (Line) Scan	Horizontal (Frame) Scan
Scan Angle Range	total 105° (+65° / -40°)	max. 360°
Scanning Mechanism	rotating multi-facet mirror	rotating head
Scan Speed ¹²⁾	4 lines/sec to 420 lines/sec	0.7/sec to 360/sec
Performance	scan time less than 30 seconds for "Panorama_6mm" (approx. 30 Mio measurements) 6 mm resolution @ 10 m distance, up to 60 scan positions per hour (including scan and image acquisition with real-time on-board registration)	
Angular Step Width ¹³⁾ Δθ (vertical), Δφ (horizontal)	0.005° $\leq \Delta\theta \leq 0.25^\circ$ between consecutive laser shots	0.005° $\leq \Delta\phi \leq 0.86^\circ$ between consecutive scan lines
User definable Resolution		
Angular Accuracy ¹⁴⁾	0.0028° (10 arcsec)	0.0028° (10 arcsec)
Angle Measurement Resolution	better 0.0007° (2.5 arcsec)	better 0.0005° (1.8 arcsec)

¹³⁾ Selectable, limits depending on the selected measuring program.

¹⁴⁾ 1-sigma value, based on target modeling, under RIEGL test conditions

Technical Data to be continued at page 8

Scanner Performance (continued)

Orientation Sensors	integrated 3-axis accelerometer, 3-axis gyroscope, 3-axis magnetometer (compass), barometer
Accuracy of the Tilt Measurement	± 0.008° ¹⁾
GNSS Receiver	integrated L1 GNSS receiver, optional external RIEGL GNSS RTK receiver (L1/L2)
Waveform Data Output (optional hardware configuration)	providing digitized echo signal information for specific target echoes hardware option to be selected in the course of the ordering process
Data Storage	integrated SSD 2 TByte, removable CF-Express card 512 GByte (1 or 2 TByte optionally available), automatic sync while scanning
Cloud Storage	Amazon S3, FTP-Server, Microsoft Azure
on-board Registration	automatic scan data registration as background process while scanning

1) 1-sigma value, for vertical scanner setup position (tilt range of ± 5°), under RIEGL test conditions.

Scanner Control

via Laser Scanner	7 inch touch screen, 1280 pixel x 800 pixel
via Mobile Device(WiFi)	„RIEGL VZi-Series“-App, available for iOS and Android
via ROS	ROS (Robot Operation System) driver available

Camera

Internal Camera	3 x 12 MPix CMOS color cameras, FOV 115° x 40° (v x h) resolution of panoramic image 199 MPixel optional on-board face and license plate detection and automatic blurring in real time before image storage
External Camera (optional)	detachable SONY ILX-LR1 & SONY SEL14F18GM lens resolution of panoramic image 137 MPixel
Panorama Camera (optional)	detachable RICOH Theta Z1 resolution of panoramic image 23 MPixel

2) To comply with the requirements of the European General Data Protection Regulation (GDPR), among others.

General Technical Data

Internal Power Supply	2 x Li-Ion hot-swap rechargeable batteries 99 Wh ³⁾ , up to 80 minutes operating time, each <0.5 kg / 1.1 lbs each
External Power Supply	input voltage 11 - 34 V DC
Power Consumption	Typ. 85 W, max. 100 W (without external devices)
Main Dimensions (width x height x depth)	173 mm x 305 mm x 184 mm
Weight	Scanner without battery 6.1 kg / 13.5 lbs
Humidity	max. 80 % non condensing @ +31 °C
Protection Class	IP64, dust-tight and splash-proof
Temperature Range Storage / Operation	-10 °C up to +50 °C / 0 °C up to +40 °C: standard operation -20 °C: continuous scanning operation if instrument is powered on while internal temperature is at or above 0 °C and still air -40 °C: scanning operation for about 20 minutes if instrument is powered on while internal temperature is at or above 15 °C and still air
Low Temperature Operation ⁴⁾	

3) The value given is the capacity of the battery according to the cell manufacturer's specifications. The capacity in application is lower.
4) Insulating the scanner with appropriate material will enable operation at even lower temperatures.

Contact us



RIEGL Laser Measurement Systems GmbH, Headquarters
RIEGL USA Inc., Headquarters North America

RIEGL Japan Ltd. | RIEGL China Ltd. | RIEGL Australia Pty Ltd. | RIEGL Canada Inc. | RIEGL UK Ltd.

RIEGL Asia Pacific Ltd. | RIEGL South America SpA | RIEGL Deutschland Vertriebsgesellschaft mbH

RIEGL France SAS